



# THE ECONOMICAL BUT HIGH QUALITY TABLES!



PVT 30

## PVT-30 SERIES

### Ironing board with vacuum or vacuum and blowing (A/S versions).

- Vacuum with high-depression motor at 0,37 KW - 0,5HP
- Electrically heated form. Special forms upon request - see page 19
- Garment holders.
- 3-layer padding. Silicon iron rest.

#### Options:

- Stainless steel swing arm with ergonomic moulding.
- Electrically heated arm forms. Vast array of forms available upon request (see page 20)
- Special arm forms upon request.
- Lighting device and iron trolley.
- Condensation separator group, with electric-steam or steam iron, or with temperature control using high-precision electronic display (see catalogue of irons)
- Anti-shine shoe in PTFE-aluminium or stainless steel
- Air-water spray gun. Steam or air/steam gun unit
- Built-in electric steam generator - capacity 8 litres - 4KW - meets PED standards (PVT-38)
- No delay in switching from vacuum to blowing, thanks to action of pneumatic cylinders

### Table de repassage aspirante ou aspirante et soufflante.

- Aspiration avec un moteur à haute dépression de 0,37 KW - 0,5HP.
- Plateau chauffée électriquement. Plateaux spéciaux sur demande - voir page 19.
- Porte-vêtements.
- Couverture à 3 couches. Repose-fer en silicone.

#### Options:

- Support janette mobile avec un façonnage ergonomique en acier inox.
- Janettes chauffées électriquement. Ample disponibilité de janette (voir page 20).
- Janettes spéciales sur demande.
- Lumière et trolley du fer à repasser.
- Groupe séparateur de buées avec le fer à repasser à électrovapeur ou vapeur ou avec le contrôle de la température avec l'affichage électronique de haute précision (voir le catalogue des fers à repasser).
- Semelle anti-brillant en PTFE-aluminium ou en acier inox.
- Groupe pistolet nébuliseur d'air-eau. Groupe pistolet à vapeur ou à air/vapeur.
- Générateur électrique de vapeur incorporé - capacité de 8 litres - 4 KW - selon les réglementations PED (PVT-38).
- Aucun retard dans le passage de l'aspiration au soufflage, grâce à l'action de cylindres pneumatiques.



388

## 388 SERIES

### Modular ironing board with vacuum or vacuum and blowing

- Super-powerful vacuum with high-depression motor at 0,6 KW - 0,8HP
- Electrically heated form. Special forms upon request - see page 19
- Garment-holders.
- Vertical air discharge chimney.
- 3-layer padding. Silicon iron support.

#### Options:

- Swing arm.
- Electrically heated arm forms. Vast array of forms available (see page 20)
- Special arm forms upon request.
- Lighting device and iron trolley, adjustable in height and depth.
- Additional iron support, adjustable in height and depth, for ironing right point
- Condensation separator group, with electric-steam or steam iron, or with temperature control using high-precision electronic display (see catalogue of irons)
- Anti-shine shoe in PTFE-aluminium or stainless steel
- Air-water spray gun. Steam or air/steam gun unit
- Built-in electric steam generator, meeting PED standards, with capacity of 5 litres - 4KW.
- No delay in switching from vacuum to blowing, thanks to action of pneumatic cylinders.

### Table de repassage modulaire aspirante ou aspirante et soufflante.

- Aspiration super-puissante avec un moteur à haute dépression de 0,6 KW - 0,8HP.
- Plateau chauffée électriquement. Plateaux spéciales sur demande - voir page 20.
- Porte-vêtements.
- Cheminée verticale d'évacuation de l'air.
- Couverture à 3 couches. Repose-fer en silicone.

#### Options:

- Support janette mobile.
- Janettes chauffées électriquement. Ample disponibilité des janettes (voir page 190).
- Janettes spéciales sur demande.
- Lumière et trolley du fer à repasser réglables en hauteur et profondeur.
- Repose-fer additionnel réglable en hauteur et profondeur pour le repassage avec la pointe à droite.
- Groupe séparateur de buées avec un fer à repasser à électrovapeur ou vapeur ou avec le contrôle de la température avec affichage électronique de haute précision (voir le catalogue des fers à repasser).
- Semelle anti-brillant en PTFE-aluminium ou en acier inox.
- Groupe pistolet nébuliseur d'air-eau. Groupe pistolet à vapeur ou à air/vapeur.
- Générateur électrique de vapeur en incorporé - capacité de 5 litres - 4KW - selon les réglementations PED.
- Aucun retard dans le passage de l'aspiration au soufflage, grâce à l'action de cylindres pneumatiques.